

AMENDMENTS TO THE CLAIMS

1-5. (Canceled).

6. (Currently Amended): A liquid crystal display (LCD) device, comprising:

an upper polarizer on a upper substrate;

a lower substrate on a lower polarizer;

a liquid crystal layer disposed between the upper substrate and the lower substrate; and

a backlight device disposed opposite and adjacent to the lower polarizer for emitting light toward the lower polarizer;

wherein the lower polarizer includes a light shielding film formed in a rectangular loop shape having a rectangular opening ~~[[only]]~~ along a peripheral portion of the lower polarizer to permit the light to pass through the rectangular opening;

wherein the light shielding film only blocks a portion of the light traveling to four sides of the lower polarizer; and

wherein the light shielding film absorbs light.

7. (Previously Presented): A liquid crystal display (LCD) device according to claim 6, wherein the light shielding film includes a coating that absorbs light.

8. (Previously Presented): A liquid crystal display (LCD) device of claim 7, wherein the light shielding film is formed by a printed material.

9. (Previously Presented): A liquid crystal display (LCD) device of claim 6, wherein the light shielding film extends along four peripheral sides of the lower polarizer.

10. (Previously Presented): A liquid crystal display (LCD) device of claim 6, wherein the light shielding film is dark.

11. (Previously Presented): A liquid crystal display (LCD) device of claim 6, wherein the light shielding film is black.

12. (Previously Presented): The liquid crystal display (LCD) device of claim 6, wherein said liquid crystal display device is a dot matrix liquid crystal display.

13. (New): A liquid crystal display (LCD) device, comprising:

- an upper polarizer on a upper substrate;

- a lower substrate on a lower polarizer, the lower polarizer having a blackened portion along a peripheral portion of the lower polarizer for minimizing constructive interference at a peripheral portion of the LCD device;

- a liquid crystal layer between the upper substrate and the lower substrate; and

- a backlight device under the lower polarizer for emitting light toward the lower polarizer.

14. (New): A liquid crystal display (LCD) device, comprising:

- an upper polarizer on a upper substrate;

- a lower substrate on a lower polarizer;

- a liquid crystal layer between the upper lower substrates; and

- a backlight device disposed opposite and adjacent to the lower polarizer for emitting light toward the lower polarizer;

wherein the lower polarizer includes a light shielding film formed in a rectangular shape only along a peripheral portion of the lower polarizer for minimizing constructive interference at a peripheral portion of the LCD device.